

AX3000 MODEL 80

(Reference: AX3-80)

Very High Graphical Performance

Overview



Designed and manufactured by AXEL, the AX3000 Terminal allows direct TCP/IP **text and graphics** connections to all popular multi-user operating systems: Windows, Unix/Linux, AS/400, S/390, etc.

This terminal is designed to be mounted on rear of a flat screen:



Main Features

Network Interface:

- Ethernet 10/100BT

Screen Session Protocols:

- RDP
- ICA/HDX
- View Client
- VNC
- telnet, ssh and tty (*)
- telnet 5250
- telnet 3270

Graphical specifications:

- Resolutions (according aspect ratio):
- . 16/10: 1440x900, 1680x1050, 1920x1200 . 16/9: 1360x768, 1600x900, 1920x1080 . 4/3: 800x600, 1024x768, 1280x960, 1280x1024, 1600x1200
- Max number of colors: True Color (24/32 bpp)

Supported USB Devices:

- Keyboards, mice, barcode readers
- Printers
- Touch Screens
- USB-RS232 and USB-Parallel Adaptors
- Smartcard readers
- Audio devices

Auxiliary Port Protocols:

- I PD
- RDP/ICA Printer and COM Port Redirection
- Prt5250 (TN5250E)
- Prt3270 (TN3270E)
- tty (client & server)
- telnet (client)
- rcmd/rsh

Centralized Administration:

- Remote set-up
- Text Remote control
- VNC Remote control
- DHCP & DNS support
- Downloading firmware (XML, BOOTP & TFTP)

Technical Information



Rear Panel Connectors:

- Power connector for the AX3000,
- VGA monitor connector,
- 2 USB ports,
- RJ45 TCP/IP 10/100BT connector.

Front Panel Connectors:

- 2 USB ports.

Weight: 330 g

Dimensions: 105x135x27 mm **Consumption (no device)**: 5 watts

Power Supply: external

AXEL: http://www.axel.com - contact: support@axel.com

^{*} Available emulations: 3151, ADDS VP-60, ADDS VP-A2, ANSI, ANSI DATA GENERAL, ANSI INTERACTIVE, ANSI RS6000, ATO300, C332, LINUX, OS2 POLYMOD2, PRISM, PROLOGUE 3, QVT119+, REAL/32, SCO OPENSERVER, SM9400, SM9412, THEOS, TVI 950, TWINSERVER, UNIX SCO 3.2.2, UNIX SCO 3.2.4, UNIX SVR4, UNIXWARE 7, VT100/VT220, VT52, WYSE 50/60/120, XENIX SCO